

The Piet Hein sloep

General information, standard equipment:

- Length 6.18 meter
 - Width 2.34 meter
 - Height 0.88 / 1.05 meter
 - Draught 0,54 meter
 - Displacement 900 – 1200 kg
 - Professional design by Martin de Jager Yachtdesign BV
 - CE-certified according to EG directives 94/25/EEG Cat. D
-
- Clinkered polyester hull, 11 strokes, 32 colours to choose
 - Fully 100% hand-lay-up, no spray-gun
 - Unsinkable by blocks of polystyrene
 - Streamlined hanging rudder
 - U-shaped front- and backbenches
 - Storage capacity underneath benches and decks
 - Round benches with sloped back
-
- 80 mm rope-fender with knotted puddening
 - Steering stand with teak STAZO-steeringwheel diam. 50cm
 - Teak fender list (70 * 20 mm) on gunwale
 - Teak rope fender support
 - Teak cockpit coming (70 * 20 mm)
 - Teak rudder pads
 - Teak cushion support around the benches
 - Teak decking on motor hood
 - Teak decking on aft hatch
 - Teak entrance steps
-
- Mitsubishi 16 HP 2-cilinder diesel, intercooler
 - Hydraulic steering mechanism
 - Water lubricated shaft system 25mm
 - Bull flex flexible clutch
 - Automatic bilge pump
 - Heavy sound & vibration insulation
 - 55 Ah maintenance free battery
 - 60 litre fuel tank
 - RPM & hour-counter
 - Round shining white light (inland-waters approval)
-
- Toilet facility in front bench
 - Cool box in aft bench
 - Waste bin underneath starboard entrance
 - SS 316 (seawater proof) cleats, clamps, hinges etc.
 - SS 316 stem band strip with laminated towing-eye
 - SS 316 rudder fittings and keel shoe
 - SS 316 Flag holder
 - Antifouling (AKZO-Sikkens 2000) below waterline